

59-1 SAN CHIA, JEN TE, TAINAN COUNTY, TAIWAN. TEL: 886-6-266-5000 FAX: 886-6-266-5555~7

Material Safety Data Sheet

April 28, 2010 V2W

Product Name: **Kibisan** [®] PN-106 L150 PN-107 L125 PN-117 L100 PN-117 L200

PN-117 L250 PN-117C PN-127 L100 PN-127 L150

PN-127 L200 PN-127H PN-137H

1.COMPANY IDENTIFICATION

Company Chi Mei Corporation

Address 59-1, San Chia, Jen Te Village, Tainan County, Taiwan, ROC. Information Phone No. 886-6-2663000 Ext.1361 (Market & Business Development) Emergency Phone No. 886-6-2663000 Ext.1361 (Market & Business Development)

Fax No. 886-6-2667981

2.COMPOSITION / INFORMATION ON INGREDIENTS

Substance or Preparation Substance

Chemical Name Acrylonitrile-Styrene Copolymer

Content >99% (Additives $\leq 1\%$)

Formula (C3H3N,C8H8)x CAS No. 9003-54-7 Impurities Contributing to Hazard None

3.HAZARD IDENTIFICATION

Most Important Hazards
Adverse Human Health Effects
Environmental Effects
None
Physical and Chemical Hazards
None

4.FIRST AID MEASURES

In case of gases evolving from melted resin, move subject to fresh air.

Treat symptomatically.

Skin Contact In case of pellets or powder, wash with water.

In case of melt, wash affected skin area and clothing with plenty of (soap and) water.

Seek medical advice.

Eye Contact In case of pellets or powder, flush with plenty of water for at least 15 minutes.

Seek medical advice if any dust particles still remain.

In case of gases evolving from melted resin of high temperature, flush with plenty of

water for at least 15 minutes. Seek medical advice if necessary.

Induce vomiting. Rinse mouth with water. Seek medical advice if necessary.

5.FIRE-FIGHTING MEASURES

Extinguishing Media Water, Foam, Dry chemical powder Special Fire-Fighting Procedure Self contained breathing apparatus

Fire and Explosion Hazards None

6.ACCIDENTAL RELEASE MEASURES

Methods for Cleaning up Recovery if not contaminated or Disposal

Personal Precautions Pellets or powder remained on ground may cause slipping

Environmental Precautions Gather pellets and powder thoroughly to avoid birds or fishes taking from

draining water.

7.HANDLING AND STORAGE

Handling Prevent from fire around handling area. Maintain good housekeeping standards to prevent

accumulation of dust. To avoid dust explosion resulting from the existence of powder, electrostatics eliminators and grounding should be fixed to such equipment as air transferring

pipes, bag filters and hoppers. Use electrically conductive filters for bag filters.

Storage Keep the materials at a cool dry place. Protect from direct sunlight, rain and violent

temperature fluctuation. Fire is inhibited around storage area.



奇美實業股份有限公司 CHI MEI CORPORATION

59-1 SAN CHIA, JEN TE, TAINAN COUNTY, TAIWAN. TEL: 886-6-266-5000 FAX: 886-6-266-5555~7

版切有限公司 IEE. 880-0-200-3000 FAX. 880-0-200-333

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Threshold Limit Value Not determined

Ventilation Necessary to exclude dust, fumes and gases.

Personal Protection Eye Wear safety glasses for general purpose. Wear chemical goggles

for cleaning molding machines.

Respiratory Wear masks for cleaning molding machines.

Gloves Necessary for handling melted resin.

9.PHYSICAL and CHEMICAL PROPERTIES

Physical form Pellets

Odor Very slight sweet aromatic

Odor threshold
pH
Not Established
Not Applicable
Boiling point
Melting/Freezing point
Softening point
Not Applicable
See Softening Point
93~110°C (200~230°F)

Solubility in water Insoluble

Solubility (non aqueous) Benzene, Acetone, Methyl Ethyl Ketone(MEK), and

Dimethyl formamide (DMF)

Specific gravity

Bulk density

Approx. 1.06 kg/m³

Approx. 300-450 kg/m³

% Volatile by weight Negligible

Evaporation rate Negligible (Butyl acetate=1)

Vapor pressure Negligible

Vapor density Negligible (Air = 1)

10.STABILITY AND REACTIVITY

Stability This is a stable material

Hazardous polymerization Will not occur Incompatibilities None known Instability conditions None known

Decomposition temperature Begins at approx. 260°C (500°F)

Decomposition products

By fire or thermal decomposition: carbon dioxide, Carbon monoxide, hydrocarbons, hydrogen cyanide, nitrogen oxides and some original

monomers such as styrene and acrylonitrile.

11.TOXICOLOGICAL INFORMATION

Irritation Fumes or vapors generated from decomposing resin may

be irritant to eyes.

Acute oral toxicity (LD50) Not determined Not determined

12.ECOLOGICAL INFORMATION

To avoid being taken by ocean species or birds, disposal of the waste to the ocean and water sources is inhibited.

13.DISPOSAL CONSIDERATIONS

Controlled incineration or landfill according to local, state or national laws and regulations concerning health and pollution.

Inadequate incineration may generate toxic gases such as CO and SM.

14.TRANSPORT INFORMATION

Not classified

15.REGULATORY INFORMATION

Not available

16.OTHER INFORMATION

None