

GHS SDS

February 14, 2011 VIW

Product Name : **Kibiton**® PB-511 PB-5301 PB-5302 PB-5502
Kibipol® PR-1205

1. COMPANY IDENTIFICATION

Company Chi Mei Corporation
Address 59-1, San Chia, Jen Te Village, Tainan County, Taiwan, ROC.
Information Phone No. 886-6-2663000 Ext.1361 (Market & Business Development)
Emergency Phone No. 886-6-2663000 Ext.1361 (Market & Business Development)
Fax No. 886-6-2667981

2. HAZARD IDENTIFICATION

Most Important Hazards None
Adverse Human Health Effects None
Environmental Effects None
Physical and Chemical Hazards None

3. COMPOSITION / INFORMATION ON INGREDIENTS

Substance or Preparation Substance
Chemical Name Styrene-Butadiene Copolymer
Content >99% (additive ≤1%)
Formula (C₈H₈,C₄H₆)_x
CAS No. 9003-55-8
Impurities Contributing to Hazard None

4. FIRST AID MEASURES

Inhalation In case of gases evolving from melted resin, move subject to fresh air. Treat symptomatically.
Skin Contact In case of pellets or powder, wash with water.
In case of melt, wash affected skin area and clothing with plenty of (soap and) water, seek medical advice.
Eye Contact In case of pellets or powder, flush with plenty of water for at least 15 minutes. Seek medical advice if any dust particles still remain.
In case of gases evolving from melted resin of high temperature, flush with plenty of water for at least 15 minutes. Seek medical advice if necessary.
Ingestion Induce vomiting. Rinse mouth with water. Seek medical advice if necessary.

5. FIRE-FIGHTING MEASURES

Extinguishing Media Water, Foam, Dry chemical powder
Special Fire-Fighting Procedure Self contained breathing apparatus
Fire and Explosion Hazards None

6. ACCIDENTAL RELEASE MEASURES

Methods for Cleaning up Recovery if not contaminated or Disposal
Personal Precautions Pellets or powder remained on ground may cause slipping
Environmental Precautions Gather pellets and powder thoroughly to avoid birds or fishes taking from draining water.

7. HANDLING AND STORAGE

Handling Prevent from fire around handling area. Maintain good housekeeping standards to prevent accumulation of dust. To avoid dust explosion resulting from the existence of powder, electrostatics eliminators and grounding should be fixed to such equipment as air transferring pipes, bag filters and hoppers. Use electrically conductive filters for bag filters.
Storage Keep the materials at a cool dry place. Protect from direct sunlight, rain and violent temperature fluctuation. Fire is inhibited around storage area.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Threshold Limit Value		Not determined
Ventilation		Necessary to exclude dust, fumes and gases.
Personal Protection	Eye	Wear safety glasses for general purpose. Wear chemical goggles for cleaning molding machines.
	Respiratory	Wear masks for cleaning molding machines.
	Gloves	Necessary for handling melted resin.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Off white pellets
Melting Temperature	Start Softening above 70 °C
Solubility	Insoluble in water
Specific Gravity	0.92 ~ 0.95

10. STABILITY AND REACTIVITY

Flammability	Yes
Flash Point	Not Applicable
Autoignition Temperature	Not Applicable
Reactivity with Water	No
Stability	Stable and non-reactive under normal handling and storage condition.
Thermal Decomposition Gases	CO, SM and NO
Combustion Energy	3.53 x 10 ⁷ J/kg (8424 Kcal/kg)

11. HEALTH HAZARD DATA

Irritation	Fumes or vapors generated from decomposing resin may be irritant to eyes.
Acute oral toxicity (LD50)	Not determined
Mutagenicity	Not determined

12. ECOLOGICAL INFORMATION

Put into containers for reclaiming or disposal.

13. DISPOSAL CONSIDERATIONS

Controlled incineration or landfill according to local, state or national laws and regulations concerning health and pollution.
Inadequate incineration may generate toxic gases such as CO and SM.

14. TRANSPORT INFORMATION

Not classified

15. REGULATORY INFORMATION

Not available

16. OTHER INFORMATION

None